



Vaso autoclave orizzontale con membrana intercambiabile per circuiti di acqua sanitaria.
 Horizontal pressure tank with replaceable membrane for pressurized systems of sanitary water.
 Réservoir sous pression horizontal à vessie remplaçable pour systèmes d'eau sanitaire.
 Horizontales Druckausdehnungsgefäß mit austauschbarer Membrane für Trinkwassersysteme.

Temperatura d'esercizio
 Working temperature
 Température d'exercice
 Betriebstemperatur

- 10° C
+ 100° C

Colore della verniciatura esterna
 External finish color
 Couleur de la peinture externe
 Externe Beendenfarbe

RAL 5015

Membrana in gomma
 Rubber membrane
 Vessie en gomme
 Gummimembrane

EPDM

Controflangia zincata - Counter flange galvanized
 Contre-bride galvanisée - Gegenflansch Verzinkt



Garanzia sul prodotto mesi: - Warranty months:
 Garantie mois: - Monate Garantie:

24

| Modello Model Modèle Model | Codice Code Code Code | Altezza Height Hauteur Höhe | Diametro Diameter Diamètre Durchmesser | Lunghezza Length Longeur Länge | Pressione massima d'esercizio Maximun working pressure Pression maximale d'exercice Maximaler Betriebsdruck | Pressione di precarica standard Standard precharge pressure Pression de précharge standard Vordruck | Imballo Packing Emballage Verpackung | Attacco Connection Raccordement Anschluss |
|-------------------------------------|--------------------------------|--------------------------------------|---|---|--|--|---|--|
| | | H (mm) | Ø (mm) | L (mm) | (bar) | (bar) | (mm) | (inch) |
| VA018 | AAGOE11B01CC1 | 305 | 280 | 430 | 10 | 1,5 | (Pz4) 520X580X610 | 1" |
| VA024 | AAIOE11B01EC1 | 300 | 280 | 483 | 10 | 1,5 | (Pz4) 520X580X610 | 1" |
| VA035 | AAJOE11B01EA1 | 376 | 365 | 440 | 10 | 1,5 | (Pz1) 380X400X460 | 1" |
| VA050 | AAKOE11B01EA1 | 380 | 365 | 585 | 10 | 1,5 | (Pz1) 380X400X590 | 1" |
| VA060 | AALOE11B01EA1 | 385 | 365 | 665 | 10 | 1,5 | (Pz1) 380X400X700 | 1" |
| VA080 | AAMOE11B01EA1 | 430 | 410 | 725 | 10 | 1,5 | (Pz1) 430X450X735 | 1" |
| VA0100 | AANOE11B11EA1 | 520 | 495 | 685 | 10 | 1,5 | (Pz1) 510X540X700 | 1" |
| VA0150 | AAPOE11B11EA1 | 585 | 550 | 820 | 10 | 1,5 | (Pz1) 570X610X850 | 1" |

Temperatura d'esercizio
 Working temperature
 Température d'exercice
 Betriebstemperatur

- 10° C
+ 100° C

Colore della verniciatura esterna
 External finish color
 Couleur de la peinture externe
 Externe Beendenfarbe

RAL 5015

Membrana in gomma
 Rubber membrane
 Vessie en gomme
 Gummimembrane

EPDM

Controflangia verniciata - Painted counter flange
 Contre-bride peinte - Lackierter Gegenflansch



Garanzia sul prodotto mesi: - Warranty months:
 Garantie mois: - Monate Garantie:

24

| Modello Model Modèle Model | Codice Code Code Code | Altezza Height Hauteur Höhe | Diametro Diameter Diamètre Durchmesser | Lunghezza Length Longeur Länge | Pressione massima d'esercizio Maximun working pressure Pression maximale d'exercice Maximaler Betriebsdruck | Pressione di precarica standard Standard precharge pressure Pression de précharge standard Vordruck | Imballo Packing Emballage Verpackung | Attacco Connection Raccordement Anschluss |
|-------------------------------------|--------------------------------|--------------------------------------|---|---|--|--|---|--|
| | | H (mm) | Ø (mm) | L (mm) | (bar) | (bar) | (mm) | (inch) |
| VA0200 | AAQOG21B11FA1 | 628 | 600 | 920 | 10 | 2 | (Pz1) 620X630X1030 | 1 1/4" |
| VA0300 | AASOG21B11FA1 | 680 | 650 | 1082 | 10 | 2 | (Pz1) 680X700X1290 | 1 1/4" |

Controflangia inox AISI 304 disponibile su richiesta. - Stainless steel AISI 304 counter flange available on request.
Contre bride inox AISI 304 disponible sur requête. - Inox Flansch AISI 304 auf Anfrage.

Marchi CE secondo la Direttiva - CE marked according to Directive - Avec la marque CE selon la Directive - CE Kennzeichnung
 2014/68/UE