



## SAR 550



### ACQUE REFLUE CHIARE - ACQUA PIOVANA

| TIPO             | POTENZA (P <sub>2</sub> ) |      | SERBATOIO<br>litri | PORTATA<br>MAX<br>(1 pompa)<br>litri/min | PREVALENZA<br>MAX<br>metri |
|------------------|---------------------------|------|--------------------|--|----------------------------|
|                  | kW                        | HP   |                    |  |                            |
| SAR 550 - TOP4 N | 0.75                      | 1    | 550                | 320                                      | 12.5                       |
| SAR 550 - TOP5 N | 0.92                      | 1.25 | 550                | 360                                      | 15                         |
| SAR 550 - RXm4   | 0.75                      | 1    | 550                | 260                                      | 15                         |
| SAR 550 - RXm5   | 1.1                       | 1.5  | 550                | 300                                      | 19.5                       |
| SAR 550 - Dm10-N | 0.75                      | 1    | 550                | 300                                      | 15.5                       |
| SAR 550 - Dm20-N | 0.75                      | 1    | 550                | 250                                      | 19                         |
| SAR 550 - Dm30-N | 1.1                       | 1.5  | 550                | 275                                      | 26                         |

### ACQUE REFLUE SPORCHE O LURIDE

| TIPO                  | POTENZA (P <sub>2</sub> ) |     | SERBATOIO<br>litri | PORTATA<br>MAX<br>(1 pompa)<br>litri/min | PREVALENZA<br>MAX<br>metri |
|-----------------------|---------------------------|-----|--------------------|--|----------------------------|
|                       | kW                        | HP  |                    |  |                            |
| SAR 550 - RXm 4/40    | 0.75                      | 1   | 550                | 280                                      | 9.5                        |
| SAR 550 - RXm 5/40    | 1.1                       | 1.5 | 550                | 380                                      | 12.5                       |
| SAR 550 - VXm10/35-ST | 0.75                      | 1   | 550                | 400                                      | 10.5                       |
| SAR 550 - VXm10/50-ST | 0.75                      | 1   | 550                | 550                                      | 9.5                        |
| SAR 550 - BCm10/50-ST | 0.75                      | 1   | 550                | 600                                      | 11                         |
| SAR 550 - VXm 10/35-N | 0.75                      | 1   | 550                | 400                                      | 10                         |
| SAR 550 - VXm 15/35-N | 1.1                       | 1.5 | 550                | 500                                      | 13.5                       |
| SAR 550 - VXm 10/50-N | 0.75                      | 1   | 550                | 550                                      | 8.5                        |
| SAR 550 - VXm 15/50-N | 1.1                       | 1.5 | 550                | 650                                      | 11                         |
| SAR 550 - BCm 10/50-N | 0.75                      | 1   | 550                | 600                                      | 11                         |
| SAR 550 - BCm 15/50-N | 1.1                       | 1.5 | 550                | 750                                      | 14                         |